





## **CT Plus™ FILTER SYSTEM**





#### **CamAir CT Plus™**

Order No.	Description
130522	CT Plus 5-stage compressed air treatment and drying center
130517	Filter element, water
130518	Filter element, coalescing
130504	DC30 desiccant cartridge



- · First stage filter removes oil, water and dirt down to 40 microns
- Second stage coalescer removes oil vapors and dirt particles down to .01 microns
- CT30 desiccant tank repeats dirt and oil aerosol removal and removes humidity

## 75 CFM capacity at 100 PSI

## Easy and economical maintenance

- Longer desiccant life
- Air inlet valve shuts off CT Plus<sup>™</sup> air without having to shut off shop air
- No tools needed to change first and second stage filters
- Easy change-out desiccant cartridge bag

## Ergonomic, self-relieving regulator

# **Complete compressed air** treatment and drying center

## **ACCESSORIES** 130516

Regulator assembly



#### 130517

Filter element, water and particulates

#### 130518

Filter element, coalescing

#### 130527

Filter element. charcoal



#### 130529 CamAir Paint Dryer and Stand



### 703086

HVLP Waterborne, 1.3

#### 703087

HVLP Waterborne, 1.4

#### 703088

High Efficiency Waterborne, 1.2 & 1.3

