



C&C INDUSTRIAL SALES

Finishing Equipment & Engineered Finishing Systems

an otp industrial solutions company

# Sanitary Equipment

Husky™ 205



- 1/4 in (6.3mm) connection
- Max flow: 5gpm (19 lpm)
- Polypropylene, PVDF

Husky™ 307



- 3/8 in (9.4mm) connection
- Max flow: 7gpm (26 lpm)
- Polypropylene

Husky™ 515



- 1/2 in (12.7mm) connection
- Max flow: 15gpm (57 lpm)
- Polypropylene, PVDF

Husky™ 1050



- 1 in (25.4mm) connection
- Max flow: 50gpm (189 lpm)
- Polypropylene, PVDF

## A COMPLETE LINE OF CHEMICAL TRANSFER PUMPS

Husky™ 15120



- 1-1/2 in (38.1 mm) connection
- Max flow: 120gpm (454 lpm)
- Polypropylene, PVDF

Hydra-Clean®



- High Pressure cleaning and sanitizing
- Air-operated and hydraulic for hazardous or confined areas 10:1, 12:1, 23:1 30:1, or 45:1 ratio options
- Available in wall, cart or drum mount packages

Husky™



- 2 in (50.8 mm) connection
- Max flow: 200gpm (757 lpm)
- Polypropylene, PVDF

SaniForce 1040e Electric Diaphragm Pumps



PTFE/EPDM Overmolded Diaphragms



PHONE: (800) 714 3982 • FAX: (615) 230-4446 • SALES@CCISINC.COM

HEADQUARTERS:  
1110 GREGORY DRIVE  
GALLATIN, TN 37066  
PHONE: (615) 230-4444

[www.ccisinc.com](http://www.ccisinc.com)

NORTH CAROLINA OFFICE:  
400 DOMINION DRIVE, SUITE 104  
MORRISVILLE, NC 27560  
PHONE: (919) 480-2850



C&C INDUSTRIAL SALES

Finishing Equipment & Engineered Finishing Systems

an otp industrial solutions company

# Sanitary Equipment

## Air- Operated Double Diaphragm Pumps



- Maximum flow rates to 150 gmp (567 lpm)
- Tri-Clamp connections
- Fluid pressure up to 120psi (8.4 bar, 0.84MPa)
- Durable, lube-free non-sticking air valve

## 3A and High Sanitation Diaphragm Pumps



- Maximum flow rates to 150 gmp (567 lpm)
- Fluid pressure up to 120psi (8.4 bar, 0.84MPa)
- Quick knockdown design for easy cleaning and draining
- Durable, lube-free non-sticking air valve
- Interchangeable flapper and ball checks
- Leak detection available

## SaniForce® Elevator



- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 1.5 to 14gpm (5.7 to 53lpm)
- Mobile and stationary options available



# SaniForce®

## Bin Evacuation Systems™ (BES)



- Evacuate materials from 300 gallon (1,135 l) containers without adding water
- Inflatable wiper seals for increased efficiency and faster change-out of bins
- Available with two sanitary diaphragm pumps or up to four sanitary piston pumps
- Pneumatic or electronic control options

## Piston Pumps



- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 1.5 to 14gpm (5.7 to 53 lpm)
- Double-ball and priming piston designs

## Drum Unloaders



- Unload materials from straight-sided or tapered drums
- Inflatable wiper seals for increased efficiency and faster change-out of drums
- Liner guard to prevent bags from entering pump
- Sanitary Flange clamps for quick disassembly

PHONE: (800) 714 3982 • FAX: (615) 230-4446 • SALES@CCISINC.COM

HEADQUARTERS:  
1110 GREGORY DRIVE  
GALLATIN, TN 37066  
PHONE: (615) 230-4444

[www.ccisinc.com](http://www.ccisinc.com)

NORTH CAROLINA OFFICE:  
400 DOMINION DRIVE, SUITE 104  
MORRISVILLE, NC 27560  
PHONE: (919) 480-2850